

POWERFUL INTEL® 12TH GEN. PROCESSORS

STYLISH APPEARANCE AND PERFORMANCE

FRONT PANEL PROTECTION
IP64 DUST & SPILL RESISTANT
FOR FRONT BEZEL TO EXTEND PRODUCT LIFE

VERSATILE I/O INTERFACES



MODEL NO.

GRAND-PRO III (II)

GRAND-PRO V (II)

GRAND-PRO VII (II)

	CPU	INTEL® CORE™ I3-1215UE PROCESSOR 10M CACHE, 4.40 GHZ	INTEL® CORE™ I5-1245UE PROCESSOR 12M CACHE, UP TO 4.40 GHZ	INTEL® CORE™ I7-1255U PROCESSOR 12M CACHE, UP TO 4.70 GHZ
	MEMORY	8GB DDR4-3200 (STD) - X 2 50-DIMM SOCKET UP TO 64GB		
	STORAGE	256 X 1 (M.2 SSD M-KEY 2242 & 2280) NVME PCI-E OR		
DISPLAY	DISPAY	15" EDP PANEL BACKLIGHT: LED		
	RESOLUTION	1024 X 768		
	BRIGHTNESS	350 CD/M2		
	COLOR	16.7M COLORS		
	TOUCH PANEL	PROJECTED CAPACITIVE TOUCH		
IO CONNECTORS	USB	USB 2.0 X 5 (REAR) X1 SIDE USB 3.2 GEN1 X 2 REAR USB TYPE-C 3.2 GEN1 X 1-POWERED USB 24V		
	COM PORT	X 4		
	CASH DRAWER	X 1 (24V RJ11)		
	AUDIO PORT	INTERNAL SPEAKER X 1 (2W)		
	LAN	X 1 (RJ45 10/100/1000 BASE-T)		
	VGA	X 1 (DB15)		
	DC IN	LOCKABLE 3-PIN DC 24V		
	POWER SUPPLY	90W DC 19V LOCKABLE 3-PIN POWER ADAPTER		
	DC IN	LOCKABLE 3-PIN DC 24V		
	OS SUPPORT	LINUX /WIN11/ WIN 11 & 10 IOT		
	OPTIONAL PERIPHERALS	VFD / 9.7" CUSTOMER DISPLAY / MSR /RFID/ IBUTTON FINGER PRINT READER/ 2D BARCODE SCANNER / WIFI		
	ENVIRONMENT	TEMPERATURE: OPERATION 32° TO 95° F (0° TO 35° C) STORAGE -4° TO 140° F (-20° TO 60° C) RELATIVE HUMIDITY: 20% TO 80% NON-CONDENSING		
	DIMENSION	364(W) X 339(H) X 229(D) MM DIMENSIONS ARE SUBJECT TO CHANGE BASED ON THE POS STAND CONFIGURATION.		
	CERTIFICATIONS	CE / FCC / LVD		
	PROTECTION	IP64 ON FRONT BEZEL		

SPECIFICATION

