

IP64 Front Protection: The front screen sealing prevents water, oil, and food debris from penetrating the display or ruining internal components.

Touch-Friendly Operation: Allows chefs or kitchen staff to tap orders with wet or gloved hands.

Fanless Design: Reduces dust intake and prevents moisture from entering through ventilation holes

Easy Sanitation: The smooth front glass or panel can be wiped down safely with commercial cleaning agents

Automatically sends specific menu items to the correct preparation stations
KDS streamlines communication between the front-of-house staff and the back-of-house cooks by linking directly with the restaurant's point-of-sale



KDS

WALL MOUNT AND POLE MOUNT OPTION AVAILABLE

	CPU	INTEL® CORE™ I3-1215UE PROCESSOR 10M CACHE,4.40 GHZ	INTEL® CORE™ I5-1245UE PROCESSOR 12M CACHE, UP TO 4.40 GHZ	HERTZ KDS 171
	MEMORY	8GB DDR4-3200 (STD) - X 2 SO-DIMM SOCKET UP TO 64GB		
	STORAGE	256 X 1 (M.2 SSD M-KEY 2242 & 2280) NVME PCI-E OR		
DISPLAY	DISPAY	17" EDP PANEL BACKLIGHT: LED		
	RESOLUTION	1920 X 1080		
	BRIGHTNESS	350 CD/M2		
	COLOR	16.7M COLORS		
	TOUCH PANEL	PROJECTED CAPACITIVE TOUCH		
IO CONNECTORS	USB	USB 2.0 X 2 (REAR) X2 SIDE USB 3.2 GEN1 X 4		
	COM PORT	X 2		
	CASH DRAWER	NONE		
	AUDIO PORT	INTERNAL SPEAKER X 1 (2W)		
	LAN	X 1 (RJ45 10/100/1000 BASE-T)		
	HEMI	X 1		
	DC IN	LOCKABLE 3-PIN DC 12V 7.5A		
	POWER SUPPLY	90W DC 12V LOCKABLE 3-PIN POWER ADAPTER		
	AUDIO	X1		
	OS SUPPORT	LINUX /WIN11/ WIN 10 IOT ENTERPRISE		
	OPTIONAL PERIPHERALS	NONE		
	ENVIRONMENT	TEMPERATURE: OPERATION (0° TO 45° C) STORAGE -4° TO 140° F (-20° TO 60° C) RELATIVE HUMIDITY: 20% TO 80% NON-CONDENSING		
	DIMENSION			

www.adler